

MiniCam

An uncomplicated keen eye



- Uncomplicated camera
- Multifunctional use
- Suitable for most monitor systems
- Length camera head 34 mm, diameter 40 mm
- For drains from 50 - 110 mm
- 90°-curves from 50 mm
- Very sharp picture
- Automatic and manual light control
- Service-friendly

MiniCam

The MiniCam is an uncomplicated and solid camera. It is small, but turns out to be an excellent keen eye, suitable for multifunctional use. In drains from Ø 50 mm - 110 mm it tracks down all problems and is not put off by right angle bends.

Multifunctional use

The MiniCam can be used in a broad range of circumstances. It inspects drains, waste pipes, sewers, transit pipes, ventilation channels and chimneys. An ideal tool to track down ruptures, saggings, roots, hidden defects and leakages.

Uncomplicated

The MiniCam is an uncomplicated camera:

- easy to use,
- solid,
- low maintenance,
- provides pictures of an excellent quality
- can be connected to most monitors, PC's and laptops with video-in connection by means of BNC connection.
- Standard connection for external recording equipment



8.4" high resolution TFT screen with USB data recorder (MPEG4)

Rioned

Rior B.V./Rioned
Postbus 5070
5004 EB Tilburg
Nederland

Tel. +31 (0)13 547 91 00
Fax +31 (0)13 547 91 04

info@rioned.com
www.rioned.com

Rioned UK Ltd
23 James Carter Road
Mildenhall, Suffolk, IP28 7DE
United Kingdom

Tel. +44 (0)1638 713800
Fax +44 (0)1638 716863

info@rioned.com
sales@rioned.co.uk
www.rioned.co.uk



Equipment

The MiniCam standard equipment:

- hose reel brake
- 30 metres of glass fibre push rod (4,5 mm on reel)
- automatic and direct light regulation
- hand-operated focus
- light weight, long life frame with anti slip and scratch free rubberpads
- closed maintenance free friction rings
- NW70 centralizer
- storage bag for connection cables

Optional

- electronic meter counter
- 8,4" high resolution TFT monitor with USB connection for digital recording (MPEG4)

Technical details

Usable	Pipes with Ø from 50 - 110 mm
Cable length	30 meter (glass fibre push rod) 4,5 mm on reel
Camera head	34 mm long, Ø 40 mm
Light sensitivity	3 Lux (LED white light)
Connectable to	Most monitors, PC's and laptops with video-in connection