



J40v2

Highly Portable Jaw Crusher

The J40v2 Jaw Crusher continues McCloskey's focus on quality, durability, and productivity. With heavy duty cheekplate design, 40" wide jaw and user-friendly control panel with excellent machine diagnostics, the McCloskey® J40v2 provides contractors with a highly portable option while meeting all production expectations. At 2.5 metres wide, it's ideal for applications that require a high degree of mobility.


Maximum productivity is delivered through the enhancements to the deeper jaw box, including a faster jaw speed and a larger gap between the crusher discharge and main conveyor feedboot.

The J40v2 retains the core values expected in a full size McCloskey Jaw Crusher, including high capacity production and heavy duty build, packaged for efficiency and mobility.

Features

- 1016mm (40") x 610mm (24") single toggle jaw
- Track
- Integrated hydraulic folding hopper
- Integrated hydraulic folding stockpiling conveyors
- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor feedboot
- Open chassis design for ease of maintenance
- Fast setup time

Dimensions and Capacities



Feeder
Folding hopper mounted over vibrating feeder with integral pre-screen. Feeder rate can be regulated manually or automatically by load sensing jaw.

Control Panel
User friendly waterproof and dustproof control panel. Allows monitoring of pressures, fluid levels and fuel consumption. Provides push button control of jaw, track and feeder functions.

36" Extended Conveyor
Extended 36" main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically.

Ideal Transport Size
At only 2.5m wide, the J40v2 is easily transported between job sites.

Optional Magnet
Optional overband magnet enables magnetic material separation from the source material.

Jaw Crusher
True 40" x 24" jaw with reversible hydrostatic drive, reversible jaw plates, and twin hydraulic ram wedge closed side setting (CSS) adjust.

Engine	225 Hp (167 kW)
Transport Height	10' 6" (3.20m)
Transport Length	45' 2.6" (13.78m)
Transport Width	8' 2.5" (2.50m)
Weight - w/ magnet & side conveyor	76,280 lb (34,600kg)
Crushing Chamber	40"(wide) x 24" (pitman opening)
Stockpile Height Main Conveyor	11' 4.2" (3.45m)
Stockpile Height Side Conveyor	8' 2" (2.50m)

©Copyright 2022 McCloskey International. All rights reserved. McCloskey is a registered trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.