

# IV. Permanent- Lifting Magnet



## Permanent- Lifting Magnets: SK-I

### Operation:

- For engineering, steel working industries, tool constructions, steel and plant construction, shipbuilding and material store

### Features:

- Perfect for lifting and transporting of flat and round material, also with sensitive surface
- Perfect reliability, because the pull-off force amounts 3 times of the recommended lifting force
- Easy switchable
- Easy handling, due to low weight
- Small sized and sturdy
- Max. application temperature 80° C
- Our service: UVV-safety-examination and repair!
- Additional eyelet for vertical transportation at extra cost available ( SK-I 300/ SK-I 600 Art.-Nr.: 47392)

Type	Measurements [mm]				Load [N]	Strength mind. [mm]	Load [N]	max Ø [mm]	max. Length	Weight [kg]	Art.-No.
	A	C	D	E							
SK-I 100	135	140	160	70	1000	15	450	100	1200x800	4	50871
SK-I 300	195	170	210	90	3000	25	1350	160	2000x1200	9	34858
SK-I 500	255	210	180	100	5000	30	2700	200	2500x1500	18	34859
SK-I 1000	355	290	375	142	10000	40	4500	350	3000x2000	43	34860
SK-I 2000	445	335	430	182	20000	55	9000	400	3500x2000	88	34862
SK-I 3000	470	425	750	260	30000	60	13500	400	3500x2000	175	43161
SK-I 5000	540	515	750	370	50000	70	22500	450	5000x3000	350	42037

