



C2R

Recirculating Cone Crusher

The McCloskey® C2R recirculating cone crusher combines the versatility of the C2 Cone Crusher with a full screening and reirculating system, allowing operators to produce a high quality crushed and screened final product with one machine.

Both the C2 & C2R have full-level features such as load and material level monitoring, full hydraulic push button Closed Side Setting (CSS) adjust and a full hydraulic relief system.

Features

- MC200 Cone
- Tracked
- Integrated hopper with folding rear door
- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor
- Fast setup time
- Open chassis design for ease of maintenance
- High speed, high throw 200Hp cone

Crushing Chamber

Built to be reliable in the toughest operating conditions, the cone on the C2R has a minimum setting of 13mm (0.5") and a maximum feed opening of 185mm (7.25")

Feeder

Heavy Duty steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone



Material Flow

Large clearance between crusher discharge and the main conveyor feedboot prevents bottlenecking.

Long Stroke (77mm)

Excellent productivity through long stroke and high speed in terms of capacity, reduction and end product shape.

Dimensions and Capacities

Engine	350 Hp (260 kW) 360 Hp (268 kW)
Cone	MC200
Feed Opening	38" (914mm)
Feeder Belt Width	42" (1050mm)
Hopper Volume	5m³ (6.5yd³)
Crusher Drive	Direct Drive
CSS Adjustment	Hydraulic
Transport Height	11' 1.2" (3.4m)
Transport Length	60' 9" (18.52m)
Transport Width	11' 5" (3.49m)
Weight	106,770 lb (48,430kg) est.
Stockpile Height Main Conveyor	13' 10.8" (4236mm)
Main Conveyor Belt Width	48" (1200mm)

©Copyright 2022 McCloskey International.

All rights reserved. McCloskey is a registered trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.