

TOPBENDER TB60



● — Tube Bender without mandrel — ●

MODELS

Art. Ref.	Description	Phase
TB 60T	Topbender TB60	Three

KIT MACHINE + TOOLING (Former & Counterbending Die)*

Art.	Machine	Tube	Radius	Formers
TB60T K2D	TB 60T	Gas inches	2 x Ø	Ø 1/2" (21.30 mm), R46 Ø 3/4" (26.90 mm), R56 Ø 1" (33.70 mm), R67 Ø 1 1/4" (42.25 mm), R90 Ø 1 1/2" (48.25 mm), R100 Ø 2" (60.30 mm), R150

* Formers in cast iron, counterbending dies in brass.

Art.	Machine	Tube	Radius	Formers
TB60T K3D	TB 60T	Gas inches	3 x Ø	Ø 1/2" (21.30 mm), R67 Ø 3/4" (26.90 mm), R82 Ø 1" (33.70 mm), R112 Ø 1 1/4" (42.25 mm), R130 Ø 1 1/2" (48.25 mm), R150 Ø 2" (60.30 mm), R190

* Formers in cast iron, counterbending dies in brass.

Art.	Machine	Tube	Formers
TB60T KOD	TB 60T	OD inches	Ø 5/8" (15.88 mm), R46 Ø 7/8" (22.22 mm), R56 Ø 1" (28.40 mm), R67 Ø 1 1/4" (31.75 mm), R82 Ø 1 1/2" (38.10 mm), R100 Ø 2" (50.80 mm), R150

* Formers in cast iron, counterbending dies in brass.

TECHNICAL DATA

Description	TB60T
Bending Radii**	10 ÷ 380 mm
Max Rotation Angle	210°
Max Bending Speed	2/4 rpm
Control	Electronic with Microprocessor
Number of Programs	30 x 9 Bends Each
Overload System Control	Yes
Voltage*	Three Phase 220 / 400 V
Motor	1.5 kW
Noise Level (machine operating)	< 70 dB
Upper Machine Body	Aluminium Alloy
Lower Machine Mainframe	Welded Steel
Foot-switch Control	Yes
Dimensions (w x h x l)	500 x 1000 x 760 mm
Weight	186 kg

* Other voltages available upon request.

** Special models for bending radii up to 500 mm (extended model) and up to 850 mm ("flipper" model) available upon request.



art. TB60T

MAXIMUM CAPACITY

Capacities based on materials with T.S. 42 Kg/mm² (psi 60.000) - Y.P. 25 Kg/mm² (psi 36.000)

Section	Material	Max Ø x wall thickness (mm)
○	Gas tubes	2" Gas x 4
○	Standard Steel tubes	60 x 4
○	Furniture tubes	60 x 4
○	Hydraulic Steel ST35	64 x 5
○	Stainless Steel AISI 304 - 316	64 x 3
○	Stainless Steel AISI 308 (food industry)	60 x 3
○	Soft Brass	60 x 6
○	Hard Copper & Aluminium	64 x 6
○	Soft Copper	64 x 6
○	Conduit tubes	63 x 4
○	Mepla, Geberit and similar tubes	50 x 4
●	Mild Steel (EN: S275JO)	35
■	Mild Steel (EN: S275JO)	14 x 60
□	Mild Steel (EN: S275JO)	25 x 50 x 3
□	Mild Steel (EN: S275JO)	50 x 50 x 3
■	Mild Steel (EN: S275JO)	30 x 30
┌	Mild Steel (EN: S275JO)	50 x 50 x 6
└	Mild Steel (EN: S275JO)	40 x 20 x 6

