

## GREASE PUMP ACCESSORIES

## INDUCTOR PLATE FOR 185 KG DRUMS

424 000

Air operated twin cylinder pump hoist for use with high viscosity and fibrous hard to pump greases. The inductor plate raises the pump and follower plate facilitating replacing an empty drum. The cylinders also exert downward force, pushing the pump and the follower plate in to the fluid aiding pump prime and minimizing material waste.

**Features:**

- Automatic shut off valve on the follower plate, stops the pump when the drum is empty.
- Two Ø 80 mm air cylinders, which greatly improves the input of fibrous and high viscosity greases into the pump, even at low temperatures.
- Air control box, with two air pressure regulators, one for pump control and the other for hoist control, lever valve for hoist up/down control and on/off push button for pump control.
- Heavy Duty two-lip aluminum follower plate with bleeder rod.

**Dimensions:**

830 x 600 x 1.320 mm (lowered).

830 x 600 x 2.230 mm (raised).

**391 000 Twin cylinder inductor plate for 185 Kg drums****424 000 Twin cylinder inductor plate with PM6, 55:1 pump for 185 Kg drums**

## DRUM COVERS

360 125 - 418 004

Very solid construction. With 2" BSP (F) thread for the pump bung adaptor.

PART No.	DRUM TYPE	DRUM EXT. Ø (MAX - MIN)	PUMP FIXATION
418 013	12,5 - 18 kg pails	310 - 265 mm	2" BSP (F)
418 002	20 kg pails	330 - 285 mm	2" BSP (F)
418 016	50 kg drums	395 - 350 mm	2" BSP (F)
418 004	50 kg drums	405 - 360 mm	2" BSP (F)
418 006	185 kg drums	610 - 565 mm	2" BSP (F)
418 026	185 kg drums	620 - 580 mm	2 x (4 x Ø 9 mm)

**Drum cover accessories**

**741 602:** Carrying handle (for covers PN 418 013 and PN 418 002).

**360 125:** Grease gun holder for drum covers.



## FOLLOWER PLATES

417 003

Eliminates air pockets and aids pump prime. Rubber flange minimizes waste. With handle for easy removal from empty drums.

PART No.	DRUM TYPE	DRUM EXT. Ø (MAX - MIN)	PUMP TUBE Ø (MAX - MIN)
417 006	12,5 kg pails	260 - 190 mm	42 - 26 mm
417 001	12,5 - 18 kg pails	298 - 260 mm	42 - 26 mm
417 005	20 kg pails	340 - 300 mm	42 - 26 mm
417 002	50 kg drums	370 - 330 mm	42 - 26 mm
417 003	50 kg drums	405 - 360 mm	42 - 26 mm
417 004	185 kg drums	590 - 550 mm	42 - 26 mm

