

# GT-3200



- Right-side or left-side pour capable.
- Front-steer, piston-style leg.
- Modular-designed operator's platform for paving in either direction. Provides machine operator maximum visibility over entire paving operation.
- Three hydraulically powered, gear-driven crawler tracks, 1.6 meters long. The GT-3200 can also be equipped with three foam-filled tires.
- All-track drive with operational speeds up to 15 meters per minute and 41.5 meters per minute for job-site mobility.
- Slipforms a 610 millimeter radius.
- Powered by a 67.9 kilowatt diesel engine.
- GOMACO G+ control system featuring self-diagnostics for grade and steering cross-slope and selective steer controls for paving accuracy and ease of operation.
- Hydraulically telescoping frame allows up to 914 millimeter lateral right-leg movement.
- 1.78 meter hydraulically driven charging auger. Auger and hopper designed with extra concrete capacity to slipform a complete radius without waiting for concrete delivery.
- Optional charging conveyor, 4.11 meter length, and 508 millimeter width, hydraulically powered, reversible with charging hopper.
- Sideshifting trimmerhead with 914 millimeters of hydraulic sideshift, 356 millimeters of hydraulic vertical adjustment.
- Quick-detach mold allows the easy interchangeability of mold profiles. One hopper can accommodate mold profiles up to 660 millimeters wide.
- Quick-detach hopper provides ease in changing the hopper to accommodate mold profiles over 660 millimeters wide.
- Transports at 2.59 meter width, 5.35 meter length, and 2.56 meter height.
- The versatile GT-3200 provides multi-application capabilities with curb and gutter, barrier wall up to one meter tall, sidewalk, recreational trail, and paving up to 1.5 meters wide.