

**E-SERIES SKID LOADER**



**SL 1640**

**GEHL**

# GEHL SL 1640

## DIMENSIONS SL1640 E NEW

Overall Operating Height (mm) .....	3.167
Height to Hinge Pin (fully raised) (mm) .....	2.438
Overall Height (to top of ROPS) (mm) .....	1.897
Ground Clearance to Chassis (mm) .....	150
Overall Length (mm) .....	2.576
Overall Length (w/o bucket) (mm) .....	1.905
Wheelbase (mm) .....	775
Dump Reach (full height) (mm) .....	410
Rollback at Ground .....	23°
Dump Angle .....	76°
Overall Width (mm) .....	909
Bucket Width (mm) .....	915
Clearance Circle (rear) (mm) .....	1.097
Clearance Circle (front, w/o bucket) (mm) .....	833
Clearance Circle (front, w/bucket) (mm) .....	1.473
Seat to Ground Height (mm) .....	879
Rollback at Full Height (°) .....	100
Dump Height (mm) .....	1.836
Departure Angle .....	30
Standard Tire Size .....	5.7x12

## ENGINE

Make .....	YANMAR
Model .....	3TNV82A
Net Power (kW) @rpm .....	24 hp (17,8) @2.400
Displacement (L) .....	1.33

## HYDRAULIC SYSTEM

Auxiliary Hydraulics - Standard (L/min) .....	38,2
Filtration .....	7 micron
Reservoir Capacity (L) .....	42

## ELECTRICAL SYSTEM

Battery .....	12-volt
Starter (kW) .....	12-volt
Alternator .....	55-amp.

## CAPACITIES AND WEIGHTS

Rated Operating Load (kg) .....	386
Rated Operating Load with opt. Counterweight (kg) .....	
Tipping Capacity (kg) .....	775
Fuel Tank (L) .....	29
Travel Speed (km/h) .....	0 - 8,9
Operating Weight - approx. (kg) .....	1.352



### Москва:

E-mail: [sale@cvh.ru](mailto:sale@cvh.ru)

### Екатеринбург:

E-mail: [ural@cvh.ru](mailto:ural@cvh.ru)

### Петербург:

E-mail: [spb@cvh.ru](mailto:spb@cvh.ru)

E-mail : [info@cvh.ru](mailto:info@cvh.ru)

Tel: +7 495 925 51 19

Web : <http://www.cvh.ru>

CVH material handling